



**CRG7101B Portable Explosion proof Searchlight**

technical parameter  
Rated voltage: DC11.1V  
Rated capacity: 4400mAh  
Rated power (LED): 3x3W  
Average service life of light source (LED):  $\geq 100000$ h  
Continuous discharge time: 8h (strong light)/16h (working light)  
Charging time: 6h (after normal use)/8h (after battery depletion)  
Battery lifespan:  $\geq 1000$  cycles  
Weight: 0.925kg  
Shell protection level: IP68 (100 meters)"



**CRG7106A/B multifunctional explosion-proof handheld light**

technical parameter  
Rated voltage: 22.2V  
Rated capacity: 2.5Ah  
Rated power: Type A 2x12W 2X6 (floodlight), Type B 1x12T2X6 (floodlight)  
Equipped with light source: LED  
Average service life: 100000 hours  
Continuous discharge time:  $\geq 5$ h (concentrated strong light)  
Charging time:  $\leq 3$ h  
Explosion proof mark: ExdialCT6 Gb  
Protection level: IP66/IP68 (1.5m, 1h)  
Weight: 1.2KG



**CRG7101 Portable Strong Explosion proof Searchlight**

technical parameter  
Rated voltage: DC11.1V  
Rated capacity: 4400mAh  
Rated power (LED): 3x3W  
Average service life of light source (LED):  $\geq 100000$ h  
Continuous discharge time: 8h (strong light)/16h (working light)/32h (strobe)  
Charging time: 6h (after normal use)/8h (after battery depletion)  
Battery lifespan:  $\geq 1000$  cycles  
Weight: 0.8kg  
Shell protection level: IP68 (100 meters)"

**CRG7101A Portable Explosion proof Searchlight**

technical parameter  
Rated voltage: DC7.4V  
Rated capacity: 4200mAh  
Rated power (LED): 4x3W\1.8 red light-emitting diodes  
Average service life of light source (LED):  $\geq 100000$ h  
Continuous discharge time: 8.5h (strong light)/17h (working light)/34h (strobe)  
Charging time: 6h (after normal use)/8h (after battery depletion)  
Battery lifespan:  $\geq 1000$  cycles  
Weight: 0.8kg  
Shell protection level: IP68 (100 meters)"



**CRG7101C Portable Strong Explosion proof Searchlight**

technical parameter  
Rated voltage: DC11.1V  
Rated capacity: 4400mAh  
Rated power (LED): 3x3W  
Average service life of light source (LED):  $\geq 100000$ h  
Continuous discharge time: 8h (strong light)/16h (working light)/32h (strobe)  
Charging time: 6h (after normal use)/8h (after battery depletion)  
Battery lifespan:  $\geq 1000$  cycles  
Weight: 0.8kg  
Shell protection level: IP68 (100 meters)"



**CRG7620 Miniature Explosion proof Flashlight**

technical parameter  
Rated voltage: 3.7V  
Rated capacity: 1900mAh  
Working current of light source: 170mA  
Strong light current: 400mA  
Power: 3W  
Average service life: 100000 hours  
Continuous discharge time:  $\geq 6$ h (strong light)/12h (working light)  
Charging time (under fully discharged condition):  $\leq 4$ h  
Battery life: 1000 cycles  
Weight:  $\leq 0.1$ kg  
Shell protection level: IP67



**CRG6071 Portable Explosion proof Searchlight**

technical parameter

Rated voltage: DC11.1V Rated capacity: 4400mAh  
 Rated power: main light source 12W/auxiliary light source  
 (2 \* 3V yellow light, white light optional)  
 Average service life of light source (LED): ≥ 100000h  
 Continuous discharge time (main light):  
 ≥ 5h (strong light)/10h (working light)/20h (flicker)  
 Continuous discharge time (auxiliary light):  
 ≥ 5h (strong light)/10h (working light)/20h (flicker)  
 Battery lifespan: ≥ 1000 cycles  
 Charging time: 2h (fast charging) 4h (slow charging)  
 Battery lifespan: ≥ 1000 cycles Weight: S1.4kg  
 Shell protection level: IP65

**CRG6055 portable multifunctional lighting device**

technical parameter

Rated voltage: DC3.7V  
 Rated capacity: 4.4Ah  
 Rated power: 3W  
 Average service life of light source (LED): ≥ 100000h  
 Continuous working time: working light ≥ 17h, light ≥ 10h  
 Continuous working time of individual camera: ≥ 8h  
 Continuous working time of working light and camera simultaneously: ≥ 5h  
 Continuous working time of strong light and camera simultaneously: ≥ 4h  
 Camera image resolution: 8 million pixels  
 Weight ≤ 0.260Kg

**CRG7620A Solid State Miniature Explosion proof Strong Light Flashlight**

technical parameter

Rated voltage: DC3.7V  
 Rated capacity: 2200mAh  
 Rated power (LED): 3W  
 Average service life of light source (LED): ≥ 100000h  
 Continuous discharge time: 8h (strong light)/16h (working light)/22h (strobe)  
 Charging time: 5h  
 Battery lifespan: ≥ 1000 cycles  
 Weight: 0.12kg  
 Shell protection level: IP68

**CRG7622 multifunctional strong light inspection flashlight (1 \* 3W-LED)**

technical parameter

Rated voltage: DC3.7V  
 "Rated capacity: 2200mAh  
 Rated power (LED): 3W  
 Average usage of light source (LED) in spring: 2100000h  
 Continuous discharge time: 9h (strong light)/18h (working light)"  
 Charging time: 6 hours  
 Weight: 0.24kg  
 Battery lifespan: ≥ 1000 cycles  
 Dimensions: 35x157mm (diameter x length)  
 Shell protection level: IP68

**CRG202 portable explosion-proof flashlight**

technical parameter

Rated voltage: DC3.7V  
 Rated capacity: 2000mAh  
 "Rated power (LED): 3W  
 Average service life of light source (LED): ≥ 100000h  
 Continuous discharge time: Type A 8h (strong light)/16h (working light)/32h (strobe)  
 B-type 4h (strong light)/8h (working light)/16h (strobe)"  
 Charging time 8h  
 Battery life ≥ 1000 (cycles) Weight 260g  
 Shell protection level IP65

**CRG7400 Multi functional Strong Explosion proof Lamp**

technical parameter

Rated voltage: DC3.7V  
 Rated capacity: 4000mAh  
 Rated power (LED): 2x3W  
 Average service life of light source (LED): ≥ 100000h  
 Continuous discharge time: 5h (strong light)/10h (working light)  
 Charging time: 6h (after normal use)/8h (after battery depletion)  
 Battery lifespan: ≥ 1000 cycles  
 Weight: 0.37kg  
 Shell protection level IP66





#### CRG7210 energy-saving strong light explosion-proof flashlight

Technical parameter

Rated voltage: DC3.7V

Rated capacity: 4000mAh

Rated power (LED): 5W

Average service life of light source (LED):  $\geq 100000$ h

Continuous discharge time: 9h (strong light)/18h (working light)

36h (strobe)

Charging time: 6 hours (after normal use)

8h (after battery depletion)

Battery lifespan:  $\geq 1000$  cycles



#### CRG5118 Strong Explosion proof Directional Light

Technical parameter

Rated voltage: DC3V

Static current:  $\leq 3$ UA

Flash frequency:  $2.5 \pm 0.5$ Hz

Maximum pulse current: 80mA

Weight: 0.1kg

Shell protection level: IP68 (100 meters)



#### CRG5116B Intelligent Explosion proof Headlight

Technical parameter

Light source specification: 3WCREE LED

Battery specification: 1800mAh polymer lithium battery

Beam brightness: 130Lm

Average lifespan of light source: 100000 hours

Continuous discharge time: 5 hours of strong light, 15 hours of working light,

and 50 hours of ultra long illumination

Charging time: 3-5 hours

Shell protection level: IP65

Weight: 115g

#### CRG5116C Miniature Explosion proof Headlight

Rated voltage: DC3.7V

Rated capacity: 2Ah

Light source power: 1W/3W

Continuous discharge time: Strong light  $\geq 8$ h, working light  $\geq 16$ h

Charging time:  $\leq 6$ h

Average service life: 100000 hours

Battery life: approximately 1000 cycles

Weight: 88g



#### CRG5116 Miniature Explosion proof Headlight

Technical parameter

Rated voltage: DC3.7V

Rated capacity: 1400mAh

Rated power: 3W

Average service life of light source (LED):  $\geq 100000$ h

Continuous discharge time: 4h (strong light)/8h (working light)

Charging time: 6 hours

Battery lifespan:  $\geq 1000$  cycles

Weight: 85g

Shell protection level: IP65



#### CRG5116A Miniature Explosion proof Headlight

Technical parameter

Rated voltage: DC3.7V

Rated capacity: 1500mAh

Rated power: 3W

Average service life of light source (LED):  $\geq 100000$ h

Continuous discharge time: 4h (strong light)/8h (working light)

Red/green/blue signal indication: 32h

Charging time: 6 hours

Battery lifespan:  $\geq 1000$  cycles

Weight: 85g

Shell protection level: IP65



**CRG5130B****Portable maintenance free strong light explosion-proof work light**

Technical parameter

Rated voltage: DC6V

Rated capacity: 5000mAh

Rated power (LED): 3W

Average service life of light source (LED):  $\geq 100000$ h

Continuous discharge time: 8h (strong light)/16h (working light)

Charging time: 8h (after normal use)/10h (after battery depletion)

Battery lifespan:  $\geq 1000$  cycles

Weight: 1kg

Shell protection level: IP65

**CRG5110 Solid State Explosion proof Strong Light Headlight**

Technical parameter

Rated voltage: DC3.7V

Rated capacity: 4400mAh (Type A), 2200mAh (Type B)

Rated power: (LED) Type A: 3W, Type B: 1W

Average service life of light source (LED):  $\geq 100000$ h

Continuous discharge time:

(Type A) 15h (strong light)/25h (working light)/50h (strobe)

Continuous discharge time:

(Type B) 4h (strong light)/6h (working light)/10h (strobe)

Charging time: 6h (after normal use)/8h (after battery depletion)

Battery lifespan:  $\geq 1000$  cycles

Weight: 0.2kg (Type A)/0.16kg (Type B)

Shell protection level: IP65

**CRG5111 Remote Directional Light**

Technical parameter

Rated voltage: DC3.7V

Rated capacity: 2000mAh

Flash frequency:  $1.5 \pm 0.5$ Hz

Average current: 160mA

Continuous working time:  $\geq 12$ h

Charging time: 8-10 hours

Weight: 0.3kg

Shell protection level: IP65

**CRG5117 Explosion proof Headlight**

Technical parameter

Rated voltage: DC3.7V

Rated capacity: 1600mAh

Rated power (LED): Main light 1W, auxiliary light 0.5W

Average service life of light source (LED):  $\geq 100000$ h

Continuous discharge time: 8h (strong light)/16h (working light)/32h (strobe)

Charging time: 6h (after normal use)/8h (after battery depletion)

Battery lifespan:  $\geq 1000$  cycles

Weight: 88g

Shell protection level: IP65

**GRG6103 high-power LED explosion-proof work light**

Technical parameter

Rated voltage: DC24V

Rated capacity: 20Ah

Light source power (LED): 30W

Average lifespan of light source (LED): over 100000h

Continuous discharge time: 30h

Charging time: 12h (after normal use)/16h (after battery depletion)

Battery lifespan:  $\geq 1000$  cycles

Weight: 14.5kg

Maximum lifting height of pole: 1.9m

Shell protection level: IP65

**GRG6103B multifunctional LED lifting work light**

Technical parameters Rated voltage: DC24V

Rated power (LED): 10x3T

Average service life of light source (LED):  $\geq 100000$ h

Continuous discharge time: 15h (strong light)/30h (working light)

Battery lifespan:  $\geq 1000$  cycles

Charging time: 10h (after normal use)/12h (after battery depletion)

Weight: 15.2kg

Maximum lifting height of pole: 1.2m~3m

Shell protection level: IP65



**CRG2025 LED Explosion proof Lightweight Mobile Light**

Technical parameter  
 Rated voltage: DG22V  
 Rated capacity: 5x2 (group) Ah  
 Light source power (LED): 50W  
 Average service life of light source (LED): 100000h  
 Continuous discharge time: an additional 16 hours  
 Charging time: ≤ 6h  
 Battery lifespan: ≥ 500  
 Weight: 6 ± 0.5kg  
 Maximum lifting height of pole: 1.28m  
 Shell protection level: IP66

**CRG2023 LED lightweight mobile light**

Technical parameter  
 Rated voltage: 14.8V  
 Rated capacity: 10Ah  
 Current: 300mA  
 Light source power (LED): 27W  
 Average service life of light source (LED): ≥ 100000h  
 Continuous discharge time: ≥ 10h  
 Charging time: ≤ 8h (after the battery is depleted)  
 Battery lifespan: ≥ 1000  
 Weight: 7kg  
 Shell protection level: IP66

**CRG6129 Explosion proof Panoramic Mobile Lighting System**

Technical parameter  
 Explosion proof mark: Exeb IBMBL1C T5 Gb  
 Protection level: IP66  
 Rated voltage: DC22.2V  
 Rated power: 180W  
 Warning light color: red blue  
 Maximum illumination of the light: 600LX at a distance of 10 meters  
 Continuous working hours: 6 hours more in strong light, work  
 Light exposure ≥ 9h, weak light ≥ 12h  
 Charging time: ≤ 5h  
 Weight: 1311Kg Height: 3.5 meters  
 External dimensions:  
 Shrinkage state → 235x230X1145 (soil 5)  
 Rising state 4765x3545 (earth 50)

**CRG6102 high-power explosion-proof work light**

Technical parameter  
 Rated voltage: DC24V  
 Rated capacity: 20Ah  
 Light source power (HID): 35W  
 Average lifespan of HID light source: ≥ 1000h  
 Continuous discharge time: 8h  
 Charging time: 12h (normal use)/16h (battery depleted)  
 Battery lifespan: ≥ 1000 cycles  
 Weight: 14.5kg  
 Shell protection level: IP65

**CRG6101B high-power LED explosion-proof work light**

Technical parameter  
 Rated voltage: DC24V  
 Rated capacity: 20Ah  
 Light source power (LED): 30W  
 Average service life of light source (LED): ≥ 100000h  
 Continuous discharge time: ≥ 30h  
 Charging time: ≤ 12h (after battery depletion)/16h (after battery depletion)  
 Battery lifespan: ≥ 1000 cycles  
 Weight: 14.5kg  
 Explosion proof grade: Exde II CT6  
 Shell protection level: IP65

**CRG6101A Explosion proof Flood Control Working Light (HID)**

Technical parameter  
 Rated voltage: DC24V  
 Rated capacity: 20Ah  
 Light source power: (Xenon lamp) 35W  
 Light source luminous flux: 3200lm  
 Average service life of light source (xenon lamp): ≥ 10000h  
 Continuous discharge time: 10h  
 Charging time: 10h (after normal use)/12h (after battery depletion)  
 Battery lifespan: ≥ 1000 cycles  
 Weight: 15kg  
 Shell protection level: IP65





**CRG2060 Mobile Lighting System**

Technical parameter

Rated voltage: 12V

Rated capacity: 24Ah

Rated power: 72W

Equipped with light source: LED

Current: 1.0A (strong light)/0.7A (working light)

Luminous flux: 5500/1m (strong light) 2200/1m (working light)

Average service life: 100000 hours

Continuous discharge time: 8h (strong light)/18h (working light)

30h (weak light)

Charging time: ≤ 10h

Battery life: 1000 cycles

Weight: 22KG

**CRG6131 scissor lighting lighthouse**

Technical parameter

Light source category: 220V

Rated power: 4x550W

Horizontal rotation: 0°~358°

Vertical rotation: 0°~135°

Protection level: IP65

Control mode: electric+remote control (30 meters)

Lifting power: hydraulic

Rising height: 10m

Folding height: 1.4m

Weight: Approximately 750kg

**CRG2027-R1 Portable Lighting System**

Technical parameters Rated voltage: DC14.8V

Rated capacity: 20Ah

Rated power (LED): 27W

Average service life of light source (LED): ≥ 100000h

Continuous discharge time of battery: ≥ 10h

Battery charging time: 9-12h

Battery lifespan: ≥ 1000 cycles

Weight: 8.9KG

Shell protection level: IP65

**CRG2060-R2 Portable Mobile Lighting System**

Technical parameter

Rated voltage: 12V

Rated battery capacity: 24Ah

Rated power: 2x27W

Average service life: 100000 hours

Continuous discharge time of battery: ≥ 8h, working light 16h

Battery charging time: 8-10 hours

Weight: 19KG

Shell protection level: IP65

**CRG3058 Multi functional Lighting System**

Technical parameter

Rated voltage: 12V

Rated battery capacity: 24A

Floodlight head power: 45W

Flood lamp head luminous flux: 5500Lm

Average service life of floodlight head: 100000h

Power of spotlight head: 25w

Spotlight head luminous flux: 3000Lm

Average service life of spotlight head: 100000h

Continuous discharge time of battery: spotlight ≥ 10.5h, flood ≥ 7.5h

Spotlight and flood ≥ 3.5h

Battery charging time: ≤ 16h

Weight: 25KG

**CRG2097-R4 Mobile Lighting System**

Technical parameter

Rated voltage: 11.1V

Rated battery capacity: 48Ah

Rated power: 4 \* 27W

Average service life: 10000h

Continuous discharge time of battery:

≥ 7h (strong light)/≥ 14h (working light) ≥ 30h (weak light)/≥ 100h (sos)

Battery charging time: 8-10 hours

Weight: 24kg

Shell protection level: IP65



**CRG2098-R4 Mobile Lighting System**

Technical parameter  
 Rated voltage: 11.1V  
 Rated battery capacity: 48Ah  
 Rated power: 4 \* 40W  
 Average service life: 10000h  
 Continuous discharge time of battery:  
 ≥ 7h (strong light) ≥ 14h (working light) ≥ 30h (weak light) ≥ 100h (s0s)  
 Battery charging time: 8-10 hours  
 Weight: 24kg  
 Shell protection level: IP65

**CRG2050 Multi functional Mobile Lighting System**

Technical parameter  
 Rated voltage of battery: DC25.9  
 Rated power of light source (LED): 2x30W  
 Average service life: 100000 hours  
 Continuous illumination time: floodlighting duration ≥ 12h  
 Spotlight illumination duration ≥ 22h  
 Flood/spotlight illumination duration ≥ 8h  
 Protection level  
 Lamp head: IP65  
 Box: IP54  
 Camera pixel: 8 million  
 Camera storage capacity: 32g  
 Battery life: approximately 500 cycles  
 Charging time ≤ 6h  
 Weight: ≤ 230g  
 Operating environment temperature: -20-40

**CRG6610 Inflatable Lighting Pole**

Technical parameter  
 Rated voltage: AC220V  
 Light source power (metal halide lamp or sodium lamp)  
 3 meters 400W (optional 600W)  
 5-meter 1000W (optional 2 \* 400W)  
 7m 1000W (optional 2 \* 600W)  
 Average service life of light source: ≥ 10000h  
 Generator power (digital silent variable frequency generator): 1000W  
 Continuous working time: 6 hours  
 Lamp post deployment time:  
 3 meters 6 seconds/5 meters 12 seconds/7 meters 18 seconds  
 Weight: 3 meters 29.2 kilograms/5 meters 32 kilograms/7 meters 36.4 kilograms  
 Shell protection level: IP65

**CRG5500****Portable strong light inspection work light**

Technical parameter  
 Rated voltage: DC3.7V  
 Rated capacity: 4000mAh  
 Rated power (LED): 3W  
 Continuous discharge time: strong light 8H/working light 35H/floodlight 42H  
 Charging time: 6h normal/8h (exhausted)  
 Battery lifespan: ≥ 1000 cycles  
 Weight: 0.79kg  
 Shell protection level: IP65

**CRG2082 Remote Searchlight**

Technical parameter  
 Rated voltage: DC12V  
 Rated capacity: 5AH  
 Light source power (HID): 35W  
 Continuous discharge time: 2h  
 Charging time: 8h  
 Battery lifespan: ≥ 1000 cycles  
 Weight: 2.6kg

**CRG5510 Hand cranked Charging**

Inspection work light  
 Technical parameter  
 Rated voltage: DC3.7V  
 Rated capacity: 4000mAh  
 Rated power (LED): 3W  
 Strong light flux: 3400lm  
 Continuous discharge time: strong light 8H/working light 35H/floodlight 42H  
 Charging time: 6h (normal)/8h (cycle)  
 Battery lifespan: ≥ 1000 cycles  
 Weight: 0.79kg  
 Shell protection level: IP65



**CRG5502 multifunctional handheld inspection light**

Technical parameter  
 Rated voltage: DC11.1V  
 Rated capacity: 2000mAh  
 Rated power (LED): 3 \* 3W  
 Average service life: ≥ 10000h  
 Continuous discharge time: 5h  
 Charging time: 8h (normal)/10h (depleted)  
 Battery lifespan: ≥ 1000 cycles  
 Weight: 0.9kg  
 Shell protection level: IP66

**CRG368 class uses strong light search lights**

Technical parameter  
 Rated voltage: 7.2V  
 Power: 9W  
 Battery capacity: 6600Ah  
 Continuous discharge time of battery:  
 Strong light ≥ 9h/working light ≥ 16h/safe light for more than 100h  
 Battery charging time: 6 hours  
 Weight: ≤ 0.75kg

**CRG4100 Portable**

Strong light inspection work light  
 Technical parameter  
 Rated voltage: DC3.7V  
 Rated capacity: 4400mAh  
 Rated power (LED): 3W  
 Average service life of light source (LED): >100000h  
 Continuous discharge time: 10h (strong light)/20h (working light)  
 Charging time: 6-8 hours  
 Battery life: >1000 cycles  
 Weight: 0.5kg  
 Shell protection level: IP66

**CRG6090 Portable Xenon Lamp**

Technical parameter  
 Rated voltage (DC): 14.8V  
 Rated capacity: 6.6Ah  
 Power: 35W  
 Average service life: >10000h  
 Continuous discharge time: Strong light >2.5h  
 Charging time: 3.5h  
 Battery life cycle: >1000 times  
 Protection level: IP65

**CRG6090A (LED) Strong light search light**

Technical parameter  
 Rated voltage: (DC) 11.1V  
 Rated capacity: 6.6Ah  
 Power: 15W  
 Working current: Strong light 1.5A Working light: 1A  
 Average service life: ≥ 10000h  
 Continuous discharge time strong light: >8h  
 Charging time: 3.5h  
 Battery life cycle: 1000 times  
 Weight: 1.4kg  
 Protection level: IP65

**CRG6116 Multi functional pocket signal light**

Technical parameter  
 Rated voltage: DC3.7V  
 Rated capacity: 4000mAh  
 Rated power (LED): 3W  
 Average service life of light source (LED): >100000h  
 Continuous discharge time: 10h (strong light)/12h (signal light)  
 Charging time: 6-8 hours  
 Battery life: >1000 cycles  
 Weight: 0.26kg  
 Shell protection level: IP65







#### CRG6117 tricolor signal light

Technical parameter  
Rated voltage: 3.7V  
Rated power: 3W  
Battery capacity: 2200mAh  
Working hours: Strong light for 2 hours/Working light for 8 hours  
Weight: 0.18kg



#### CRG369 Hand cranked Multi functional Emergency Light

Technical parameter  
Rated voltage: 3.7V  
Battery capacity: 1000mAh  
Searchlight illumination time:  
Hand cranked for one minute>15min, fully charged battery>10h  
Lamp illumination time:  
Hand cranking for one minute ≥ 6min, fully charged battery>3.5h  
Radio reception time:  
Hand cranking for one minute ≥ 6min, fully charged battery>10h  
Weight 0.36KG



#### CRG5511LED rechargeable camping light

Technical parameters Rated voltage: DC7.4V  
Rated capacity: 1800mAh  
Light source power (HID): 5W  
Average lifespan of HID light source: ≥ 10000h  
Continuous discharge time: 10h  
Charging time: 6-8 hours  
Shell protection level: IP65

#### CRG168 lifting maintenance light

Technical parameter  
Rated voltage: 21V  
Rated capacity: 10Ah  
Working voltage (LEO bulb): 24/36V  
Rated power (LED): 60W  
Luminous flux (LED): 7800/1m  
Average service life: 100000 hours  
Continuous discharge time of spotlight: 8h (strong light)/16h (working light)  
Continuous discharge duration for spotlight: 16h (spotlight)/12h (spotlight)  
Charging time: 8h (after normal use)/≤ 10h (after battery depletion)  
Battery life: 1000 cycles  
Dimensions: 1200x150x2200mm  
Weight: 8kg



#### CRG6016 portable lifting work light


Technical parameter  
Rated voltage: AC220V  
Light source power: 2x500W  
Continuous working hours: Long term connection to mains power  
Pole lifting height: 1.5m-2.8m  
Dimensions: 680x150x440mm  
Weight: 8kg



#### CRG6119LED Multi functional Mobile Lighting Platform

Technical parameters Rated voltage: DC21.6V  
Rated capacity: 34Ah  
Service life: approximately 1000 cycles  
Rated power: 60Wx2  
Service life: 100000 hours  
Lighting form: adjustable spotlight/floodlight  
Dimming form: 10% -100% infinite dimming  
Warning light color: red blue warning  
Continuous lighting time: ≥ 8h  
Charging time: ≤ 8h  
Weight: 20 ± 1kg  
Amplifier (speaker) power: 30W  
Wireless Bluetooth connection distance: 30m  
Protection level: Lamp head: IP66 Box body: IP65

Contracted state



extend state

**CRG6018 portable lifting work light**

Technical parameter  
 Rated voltage: AC220V  
 Light source power: 4x500W  
 Continuous working hours: Long term connection to mains power  
 Pole lifting height: 1.5m-2.8m  
 Dimensions: 680x150x440mm  
 Weight: 8kg

**CRG6019 portable lifting lighting lamp**

Technical parameter  
 Rated voltage: AC220V  
 Light source power (metal halide lamp): 2x150W  
 Continuous working hours: Long term connection to mains power  
 Pole lifting height: 1.5m-2.8m  
 Weight: 13kg

**CRG6700 lifting floodlight work light**

Technical parameter  
 Rated voltage: AC220V  
 Light source power (metal halide lamp): 2x150W  
 Continuous working hours: Long term connection to mains power  
 Pole lifting height: 1.5m-2.8m  
 Weight: 13kg

**CRG5602 LED omnidirectional mobile work light**

Technical parameter  
 Working voltage: AC220N/50HZ  
 Lamp head power: 2 \* 150W LED  
 Lamp head luminous flux: 35000lm  
 Municipal power supply: long-term  
 Generator power/mailbox capacity: 700W/2.1L  
 Filling the generator set with fuel once: 6 hours  
 Rise/fall time: ≤ 3 minutes  
 Fuel type: 92 # gasoline  
 Generator type: Digital silent gasoline generator  
 Minimum height: 1700m, maximum raised height: 5000m  
 Protection level: IP66 (lamp head)/IP54 (lamp housing)  
 Size: 800x600x2000m  
 Weight: 50Kg

**CRG6110C omnidirectional automatic floodlight work light (SJJ)**

Technical parameter  
 Rated voltage: AC220V  
 Light source power (Osram metal halide lamp): 2x400W  
 Continuous working time: 13h  
 Rated output power of generator set: 2000W  
 Rated capacity of fuel tank: 15L  
 Weight: 45kg  
 Shell protection level: IP65

**CRG6309A lightweight lifting floodlight**

Technical parameter  
 Rated voltage: AC220V  
 Light source power (metal halide lamp): 2x150W  
 Continuous working time: 6h (long time connected to mains power)  
 Rated output power of generator set: 650W  
 Rated capacity of fuel tank: 4.2L  
 Weight: 38kg

**CRG5600 omnidirectional automatic floodlight work light**

Technical parameter  
 Rated voltage: AC220V  
 Light source power (halogen lamp head): 4x500W  
 Continuous working time: 13h  
 Rated output power of generator set: 2000W  
 Rated capacity of fuel tank: 15L  
 Weight: 45kg  
 Shell protection level: IP65

**CRG5601 omnidirectional automatic floodlight work light**

Technical parameter  
 Rated voltage: AC220V  
 Light source power (halogen lamp head): 4x1000W  
 Continuous working time: 13h  
 Rated output power of generator set: 5000W  
 Rated capacity of fuel tank: 25L  
 Weight: 85kg  
 Shell protection level: IP65



**CRG5600 all-round automatic floodlight work light (LED version)**

Technical parameter  
 Rated voltage: AC220V  
 Light source power: 4X100W (LED)  
 Continuous working time: 13h  
 Rated output power of generator set: 2000W  
 Rated capacity of fuel tank: 15L  
 Maximum height of air rod: 4.5m  
 Generator set output voltage: AC220V  
 Dimensions of the telescopic air rod: 1350x50x800mm  
 Lamp panel dimensions: 500x470x380mm  
 Weight: 45kg  
 Shell protection level: IP65

**CRG909360 panoramic mobile lighting**

Technical parameter  
 Rated power: 150W  
 Rated voltage: 22.2V  
 Color temperature: 6500K  
 Luminous flux: 4150-11000LM  
 Lithium battery capacity: 54 Ah (imported lithium battery)  
 Charger: Input: AC100-240V 50-60Hz  
 Output: DC 25.2V2A  
 Charging time: approximately 6 hours  
 Working hours: Strong light discharge time: about 4H  
 Mid light discharge time: about 8H;  
 Low light discharge time: about 16H  
 Material: Aviation grade aluminum alloy 6061-T6  
 Height adjustment range: 110-3500mm  
 Weight: 9kg

**CRG2026LED Lightweight Mobile Light**

Technical parameter  
 Rated voltage of battery: DC21.6V  
 Rated battery capacity: 13Ah  
 Rated power of light source (LED): 35W;  
 Service life: 100000 hours  
 Continuous lighting time: >8h  
 Charging time: <6h  
 Battery life: approximately 100 cycles  
 Weight: <8kg  
 Protection level: P65 (lamp head) 1P54 (box)

**CRG6121 multifunctional lifting work light**

Technical parameter  
 Light source power: 2x48W (LED)  
 Average service life: 100000 hours  
 Continuous working time: 5.5 hours (filled with oil at once)  
 Generator output power: 700W  
 Generator mailbox capacity: 1.55L  
 Weight approximately: 23kg  
 Shell protection level: IP65

**CRG6608 Ball shaped Lighting Lamp**

Technical parameter  
 Rated power: 2x1000W  
 Halogen lamp engine power: 8hp  
 Fuel tank capacity: 15L  
 Continuous working time: 13h  
 Rated power: 2.0KVA  
 Insulation level: B  
 Weight: 48kg

**CRG6105 LED portable mobile light**

Technical parameter  
 Rated voltage: DC14.8V  
 Rated capacity: 10Ah  
 Rated power (LED): 9 \* 3W  
 Average service life of light source (LED): >100000h  
 Continuous discharge time: 10h (strong light)/18h (working light)  
 Charging time: 8-10 hours  
 Battery life: >1000 cycles  
 Weight: 6.5kg  
 Shell protection level: IP65

**CRG6106 lightweight mobile lifting work light**

Technical parameter  
 Rated voltage: DC14.4V  
 Rated capacity: 10Ah  
 Rated power: 8 \* 3W=24W  
 Average service life of light source (LED): >100000h  
 Charging time: 8h (normal use)/12h (battery depleted)  
 Battery life: >1000 cycles  
 Shell protection level: IP66



**CRG6107 LED portable mobile light**

Technical parameter  
 Rated voltage: 14.8V  
 Rated capacity: 12Ah  
 Rated power: 45W  
 Average service life of light source (LED): >100000h  
 Continuous discharge time:  
 12 hours of strong light, 30 hours of working light, 60 hours of strobe light  
 Charging time: 8 hours after normal use, 10 hours when the battery is depleted  
 The battery has a lifespan of approximately 2000 cycles  
 Weight 7kg

**CRG5607 scissor type mobile lighting lamp**

Technical parameter weight: <750KG  
 Rated power: 4 \* 550W  
 Rated power: 5000W  
 Walking wheels and quantity: 4 walking wheels (detachable)  
 Voltage: 220V  
 Frequency: 50Hz  
 Power: 5000W  
 Vehicle protection level: IP54  
 Protection level: IP65

**CRG5608 all-round hydraulic lifting lighting lighthouse**

Technical parameter  
 Rated power: 7.2KW  
 Frequency: 50Hz  
 Generator insulation level: H level  
 Rated voltage: 230V  
 Fuel tank working time: 40 hours  
 Lighting power: 4x

**CRG5609 Self dumping Hydraulic Mobile Lighting Lighthouse**

Technical parameter  
 Weight: <600Kg  
 Lamp power: 2x350W+2x1000W  
 Shell protection level: IP65  
 Wind resistance level: Level 8  
 Continuous working time: 25h  
 Voltage: 220V  
 Frequency: 50Hz  
 Power: 5KW

**CRG4830 double-sided directional light**

Technical parameter  
 Rated voltage: 3.7V  
 Rated capacity: 1.5Ah  
 Continuous working time: normally on for 12 hours, flicker for 30 hours  
 Charging time: ≤ 6h  
 Average service life: 100000 hours  
 Battery life: approximately 1000 cycles  
 Weight: 800g  
 Protection level: IP65

**CRG2076 Remote Control Searchlight (HID)**

Technical parameter  
 Rated voltage: DC12V/DC24  
 Light source power (HID): 35W  
 Weight: 3.8kg

**CRG2099 Multi functional Search Light**

Technical parameter  
 Rated voltage: DC12V/DC24  
 Light source power (LED): 35W  
 Weight: 3.8kg

**CRG2099A Multi functional Search Light**

Technical parameter  
 Rated voltage: DC12V/DC24  
 Light source power (LED): 50W  
 Weight: 3.8kg



**CRG4831 double-sided directional light**

Technical parameter  
 Rated voltage: DC3.7V  
 Signal light source (LED) operating voltage: 3~4.2V  
 Working current: 100mA  
 Average service life: >100000h  
 Weight: 0.8kg  
 Shell protection level: P65

**CRG5280 Lightweight Multi functional Strong Light (LED)**

Technical parameter  
 Rated voltage: DC11.1V  
 Rated capacity: 4000mAh  
 Rated power: 3x3W  
 Average service life of light source (LED): >100000h  
 Continuous discharge time: 8h (strong light)/16h (working light)  
 Charging time: 6h (after normal use)/8h (after battery depletion)  
 Battery life: >1000 cycles  
 Weight: 1.5 kg  
 Shell protection level: IP65

**CRG5280A Lightweight Strong Light Work Light**

Technical parameter  
 Rated voltage of battery: DC11.1V  
 Rated battery capacity: 5Ah  
 Rated power: 12W  
 Continuous discharge time of battery  
 Strong light>10h, working light>24h, weak light>80h  
 Battery charging time: <3.5h  
 Battery life: >1000 cycles  
 Shell protection level: 1P66  
 Weight: 1.8 ± 0.2kg

**CRG5281 Lightweight Loading and Unloading Light**

Technical parameter  
 Rated voltage: DC14.8V  
 Rated capacity: 4400mAh  
 Rated power: 12W  
 Average service life of light source (LED): >100000h  
 Continuous discharge time: 8h (strong light)/16h (working light)  
 Charging time: 6 hours  
 Battery life: >1000 cycles  
 Weight: 1.45 kg  
 Shell protection level: IP65

**CRG5282 Lightweight Loading and Unloading Light**

Technical parameter  
 Rated voltage: 11.1V  
 Rated capacity: 4.4Ah  
 Rated power: 10W  
 Average service life: 100000 hours  
 Discharge time: 8h strong light/16h working light/32h energy-saving light  
 Battery life: 1000 cycles  
 Charging time: 6 hours  
 Protection level: IP65  
 Weight: 1.2Kg

**CRG86 Multi functional Rod Lamp**

Technical parameter  
 Rated voltage: DC3.7V  
 Rated power (LED): Floodlight: 6W  
 Flashlight spotlight: 4W  
 Rated capacity: 5000mAh  
 Average service life of light source (LED): >100000H  
 Continuous illumination time: Floodlight: Strong light>12H, working light>160H Spotlight: Strong light>15H, working light>30H, strobe>24H  
 Charging time: 6H  
 Average battery life: 100000 cycles  
 Dimensions: 260x41.2x43.5mm (length x width x height)  
 Weight: >270g  
 Shell protection level: IP66

**CRG88 Magnetic Inspection Lamp**

Technical parameter  
 Rated voltage: DC7.4V  
 Rated power (LED): floodlight 9W/spotlight 3W  
 Rated capacity: 5000mAh  
 Average service life of light source (LED): >100000H  
 Continuous illumination time: Floodlight: Strong light>3.5H, working light>5.5H Spotlight: Strong light>20H, working light>35H, strobe>24H  
 Charging time: 6H  
 Average battery life: 1000 cycles  
 Weight: ≥ 0.7Kg  
 Shell protection level: IP65





**CRG9118-1 eight band light source**

Flashlights: 8 pieces  
Filters: 7 pieces  
Tripod: 1 piece  
Charger: 1 unit  
Glasses: 3 pairs  
High end aluminum: 1 piece

**CRG9116 handheld thirteen band light source**

Power supply: DC 12v,50Hz  
Power: 75W  
White light color temperature: 8000K

**CRG7632 Wireless Charging Strong Light Inspection Flashlight**

Technical parameter  
Rated voltage: DC3.7V  
Rated capacity: 2.6Ah  
Continuous discharge time: Strong light:>8h  
Charging time: ≤ 6h  
Average service life: 100000 hours  
Battery life: approximately 1000 cycles  
Protection level: IP66  
Weight: 232g

**CRG7118 Police Strong Light Dazzling Device**

Technical parameter  
Switch mode: strong light/flash  
Power supply: 4400mA rechargeable lithium battery  
Working voltage: 7.4V  
Working current: Strong light 1.1A, weak light 400mA  
Lighting time: Strong light for 120 minutes  
Weak light for 240 minutes, burst flash for 120 minutes  
Weight: 350g

**CRG7117 strong xenon flashlight**

Technical parameter  
Rated voltage: DC9-16V  
Rated capacity: 7800mAh  
Light source power (HID): 85W/65W/45W three level dimming  
Average lifespan of HID light source:>10000h  
Continuous discharge time: 1.5h  
Charging time: 6-8 hours  
Weight: 3.5kg (aluminum alloy)  
Shell protection level: IP66

**CRG7119 Strong Xenon Lamp**

Technical parameter  
Rated voltage: DC9-16V  
Rated capacity: 4400mAh  
Light source power (HID): 35W  
Average lifespan of HID light source:>10000h  
Continuous discharge time: 1.5h  
Charging time: 6-8 hours  
Shell protection level: IP66

**CRG56 solar multifunctional rescue flashlight**

Technical parameter  
Rated voltage: DC3.7V  
Rated capacity: 3700mAh  
Rated power (LED) 10W  
Average service life of light source (LED):>100000h  
Continuous discharge time: 4h (strong light)  
Charging time: 4h Battery life:>1000 (cycles)  
Dimensions: 45x215mm (diameter x length)  
Weight: 294g  
Shell protection level: IP66

**CRG110 police strong light flashlight**

Technical parameter  
Rated voltage: DC3.7V  
Rated capacity: 2200mAh  
Rated power (LED): 3W  
Average service life of light source (LED):>100000h  
Continuous discharge time: 6h (strong light)/12h (working light)  
5% low light usage time: 6540min  
100% strong light usage time: 450min  
10Hz burst flash usage time: 516min  
Charging time: 6-8 hours  
Battery life:>1000 cycles  
Weight: 0.16kg  
Shell protection level: IP67



**CRG110A Police Strong Light Flashlight (Basic Type)**

Technical parameter  
 Rated voltage: DC3.7V  
 Rated capacity: 2200mAh  
 Rated power (LED): 3W  
 Average service life of light source (LED): >100000h  
 Continuous discharge time: 6h (strong light)/12h (working light)  
 5% low light usage time: 6540min  
 100% strong light usage time: 450min  
 10Hz burst flash usage time: 516min  
 Charging time: 6-8 hours  
 Battery life: >1000 cycles  
 Weight: <230g (including battery)  
 Shell protection level: IP67

**CRG110B Police Strong Light Flashlight (Tactical Type)**

Technical parameter  
 Rated voltage: DC3.7V  
 Rated capacity: 2200mAh  
 Rated power (LED): 3W  
 Average service life of light source (LED): >100000h  
 Continuous discharge time: 6h (strong light)/12h (working light)  
 5% low light usage time: 6540min  
 100% strong light usage time: 450min  
 10Hz burst flash usage time: 516min  
 Charging time: 6-8 hours  
 Battery life: >1000 cycles  
 Weight: <230g (including battery)  
 Shell protection level: IP67

**CRG1100A multifunctional camera flashlight**

Technical parameter  
 Rated voltage: DC3.7V  
 Rated capacity: 4200mAh  
 Rated power (LED): 3x3W  
 Average service life of light source (LED): >100000h  
 Photo pixel: 300K pixels  
 Shell protection level: IP65

**CRG7120 handheld ultra wide uniform light survey lamp**

Technical parameter  
 Rated voltage: DC7.4V  
 Rated capacity: 4000mAh  
 Rated power (LED): 10W  
 Average service life of illuminated ED: >100000h  
 Continuous discharge time: 2.5h (strong light)/5h (weak light)/10h (strobe)  
 Charging time: 8h (after normal use)/10h (after battery depletion)  
 Battery life: >1000 cycles  
 Shell protection level IP65  
 Weight 0.84kg

**CRG7112 Portable LED Uniform Survey Light**

Technical parameter  
 Rated voltage: DC7.4V  
 Rated capacity: 6.6AH  
 Rated power (LED): 10W  
 Battery life approximately: 1000 cycles  
 Continuous working time: 5h (search light) \ 10h (photography light)  
 Charging time: 6 hours  
 Protection level: IP65  
 Weight: 1.1kg

**CRG7113 portable uniform light survey lamp**

Technical parameter  
 Rated voltage: DC7.4V  
 Rated capacity: 6.6AH  
 Rated power (LED): 10W  
 Battery life: approximately 1000 cycles  
 Continuous working time: 5h (search light) \ 10h (photography light)  
 Charging time: 6 hours  
 Protection level: IP65  
 Weight: 1.1kg



**CRG7116 four band uniform light survey lamp**

Technical parameter  
 Rated voltage: DC3.7V  
 Light source lifespan: 10000h  
 Battery specification: 6600mAh  
 Battery life: 1000 cycles  
 Continuous discharge time: strong light for 8 hours  
 Charging time: 6-8 hours  
 Weight: 1.1kg

**CRG6110 single police duty warning shoulder light**

Technical parameter  
 Battery capacity: 3.7V/600mAh  
 Continuous work: >11h  
 Waterproof rating: IP66  
 Pulse current: 20mA (maximum per unit)  
 Light intensity: 7000mcd (maximum per unit)  
 Color: Red and Blue (standard), Yellow and White (optional)  
 Flashing frequency: 25Hz  $\pm$  2Hz, red blue phase difference of 0.8S  
 Temperature: -20  $^{\circ}$ C -60  $^{\circ}$ C  
 Appearance size: 80mmX37mmX33mm  
 Anti drop height: 1.5m  
 Weight: 54.5g

**CRG9120 portable LED uniform light survey lamp**

Technical parameter  
 Rated voltage: DC8.4V  
 Rated capacity: 7800mAh  
 Rated power: 30W  
 Light source type: CREE imported LED from the United States  
 Service life: 100000 hours  
 Luminous flux: >1200lm (search light)/6001m (illumination light)  
 Switch mode: Strong light/Working light/Off  
 Lighting time:  $\geq$  4h  
 Charging time: 6 hours  
 Protection level: IP66  
 Weight: 1255g (including battery)

**CRG-12W280 lifting light**

Technical parameter  
 System voltage: DC12V  
 Light source voltage: DC12V  
 Light source power (single): 80W  
 Light source rotation express: 4 revolutions per minute  
 Light source luminous flux: 10000LM  
 Light source category: Corey, USA  
 Light source lifespan: 100000  
 Equipment weight: 37KG


**CRG-18W4120 Car Lift Lighting**

Technical parameter  
 System voltage: DC12V  
 Light source voltage: DC12V  
 Light source power (single): 120W (4 in total)  
 Push rod working current:  $\leq$  12 A (max)  
 Working current of gimbal: <2 A (max)  
 Product size: 1140x680x220  
 Lamp working height: 1200mm  
 Light source rotation radius: 340MM  
 Horizontal rotation angle of light source: 380  
 Vertical rotation angle of light source: 380  
 Light source rotation express:  
 4 revolutions per minute Light source luminous flux: 60000LM  
 Light source color temperature: 6000K  
 Light source category: Corey, USA  
 Light source lifespan: 100000  
 Control mode: wired, wireless, 485  
 Equipment weight: 40KG  
 Host packaging size: 1180x370x230MM

**CRG-12W480 Car Lift Lighting**

Technical parameter  
 System voltage: DC12V  
 Light source voltage: DC12V  
 Light source power (single): 80W (4 in total)  
 Light source rotation express: 4 revolutions per minute  
 Light source luminous flux: 40000LM  
 Light source category: Corey, USA  
 Light source lifespan: 100000  
 Control mode: wired, wireless, 485  
 Equipment weight: 40KG



**CRG-12W2120 lifting lighting lamp**

Technical parameter  
 System voltage: DC12V  
 Light source voltage: DC12V  
 Light source power (single): 120W  
 Light source rotation express: 4 revolutions per minute  
 Light source luminous flux: 12500LM  
 Light source category: Corey, USA  
 Light source lifespan: 100000  
 Control mode: wired, wireless, 485  
 Equipment weight: 37KG

**CRG9112-1 Wide Footprint Search Light**

Technical parameter  
 Light source: 150W high-power LED  
 Working voltage: 30V  
 Power supply form:  
 built-in rechargeable lithium battery/dual-purpose AC/DC  
 Weight: 1500g  
 Configuration: AC/DC charger, aluminum alloy box

**CRG18W2180 car mounted lifting lighting lamp**

Technical parameter  
 System voltage: DC12V  
 Light source voltage: DC12V  
 Light source power (single): 80W  
 Light source rotation express: 4 revolutions per minute  
 Light source luminous flux: 10000LM  
 Light source category: Corey, USA  
 Light source lifespan: 100000  
 Control mode: wired, wireless, 485  
 Equipment weight: 41KG

**CRG18W2120 car mounted lifting lighting lamp**

technical parameter  
 System voltage: DC12V  
 Light source voltage: DC12V  
 Light source power (single): 120W  
 Light source rotation express: 4 revolutions per minute  
 Light source luminous flux: 12500LM  
 Light source category: Corey, USA  
 Light source lifespan: 100000  
 Control mode: wired, wireless, 485  
 Equipment weight: 41KG

**CRG9112-2 Wide Footprint Search Light**

Technical parameter  
 Rated voltage: DC12.6V/AC220V  
 Rated capacity: 7800mAh  
 Power supply form:  
 built-in rechargeable lithium battery/dual-purpose AC/DC  
 Working hours: Lighting time:>2.5h  
 Weight: 1100g (including battery)  
 Configuration: AC/DC charger, aluminum alloy box



## Fixed explosion-proof type



### CRG9881 Explosion proof Camera Flood Light

Technical parameter  
 Rated voltage: AC85V-265V  
 Rated power (LED): standard 200W, optional 100W  
 Protection level: IP66  
 Weight: 3.25kg  
 Camera parameters  
 Rated voltage of camera: AC220V/50Hz  
 Camera Pixel: 2 million  
 Optical zoom: 20x  
 Wide angle lens: >40  
 Temperature range: -20~+30 °C  
 Network mode: AP mode/station mode  
 Hotspot distance: <60m



### CRG9882 LED Explosion proof Platform Light

Technical parameter  
 Rated voltage: AC85V-265V  
 Rated power (LED): 50W standard, 30W optional  
 Protection level: IP65  
 Weight: 3.7kg



### CRG9883 Explosion proof Projection Lamp

Technical parameter  
 Rated applied voltage: AC85V-265V  
 Rated power (LED): standard 200W, optional 100W, 150W  
 Protection level: IP66  
 Weight: 2.35kg



### CRG9170B factory energy-saving explosion-proof lamp

Technical parameter  
 Rated voltage: AC220V/50Hz  
 Rated power (energy-saving lamp): 45W  
 Protection level: IP65  
 Weight: Lamp 2.1kg

## Fixed explosion-proof type



### CRG9161 Explosion proof Platform Light

Technical parameter  
 Rated voltage: AC220V/50Hz  
 Rated power (metal halide lamp/sodium lamp): 250W/150W  
 Protection level: IP65  
 Weight: 7.5kg



### CRG9820 Explosion proof Strong Light Floodlight for Interior Field

Technical parameter  
 Rated voltage: AC220V/50Hz  
 Rated power (metal halide lamp/sodium lamp): 70W/150W  
 Protection level: IP65  
 Weight: Lamp body: 3.5kg  
 Explosion proof rectifier box: 5.1kg



### CRG9885 LED Explosion proof Road Light

Technical parameter  
 Rated voltage: AC90~305V  
 Rated power (LED): standard 150W, optional 100W, 150W, 200W, 300W  
 Protection level: IP66  
 Weight: 8.8kg

### CRG9880 Explosion proof Maintenance free LED Flood Light

Technical parameter  
 Light source: Imported Korui LED beads  
 Power: 50W/100W/150W  
 Luminous flux: 120LM/W  
 Explosion proof mark: ExdembIICT4 Gb/DIP A20 TA, T4  
 Protection level: IP65  
 Anti corrosion grade: VF2  
 Installation methods: wall mounted, ceiling mounted, street lamp mounted  
 Suitable installation height: 7-12 meters  
 Lamp shell material: die cast aluminum shell  
 Material of lampshade: tempered glass  
 Lamp shell color: yellow  
 Lamp size: length 338mm, width 242mm, height 158mm  
 Gross weight: 5.6Kg





## Fixed professional category



### CRG9886A floodlight

Technical parameter  
Rated voltage: AC85V-265V  
Rated power (LED):  
Protection level: IP65  
Weight: 4.5kg



### CRG9886B floodlight

Technical parameter  
Rated voltage: AC85V-265V  
Rated power (LED):  
Protection level: IP65  
Weight: 7.5kg



### CRG9886C floodlight

Technical parameter  
Rated voltage: AC85V-265V  
Rated power (LED):  
Protection level: IP65  
Weight: 11.5kg



### CRG9886D floodlight

Technical parameter  
Rated voltage: AC85V-265V  
Rated power (LED)  
Protection level: IP65  
Weight: 16.5kg



### CRG9810 high ceiling light

Technical parameter  
Rated voltage: AC220V/50Hz  
Rated power (metal halide lamp/sodium lamp):  
BFC9810: 400W; BFC8810A: 250W  
Protection level: IP65  
Weight: 8kg



### CRG9889 Tower Pendant

Technical parameter  
Rated voltage: AC110V-260V  
Power: 100-500w  
Protection level: IP65



### CRG9121 high-power LED ceiling light

Technical parameter  
Rated voltage:  
BJQ9121 type: AC85-260V/50Hz  
BJQ9121A type: DC15-36V/50Hz  
Protection level: IP65  
Weight: 1.2kg



### CRG9178 energy-saving low ceiling light

Technical parameter  
Rated voltage: BFC9178: AC/DC220V  
Rated power: 5x3W  
Protection level: IP65  
Weight: 0.38kg



### CRG9700 Longevity Endless Lamp

Technical parameter  
Rated voltage: AC220V/50Hz  
Rated power: 40W (extreme fluorescent lamp)  
Protection level: IP65  
Weight: 3.5kg



### CRG87 Tent Light

Technical parameter  
Rated voltage: DC: 5V  
Rated capacity: 5200mAh  
Rated power (LED): 5W  
Average service life of light source (LED): >100000h  
Continuous discharge time: 9-80h  
Charging time: 3 hours  
Battery life: >1000 cycles  
Dimensions: 80 \* 80 \* 60mm  
Weight: 0.190kg  
Shell protection level: IP66



**CRG9808 shockproof floodlight**

Technical parameter  
 Rated voltage: AC220V/50Hz  
 Rated power (metal halide lamp/sodium lamp) Type A:  
 1000W/Type B: 400W  
 Protection level: IP65  
 Weight: Type A: 10.2kg; Type B: 7 kg

**CRG9803 shockproof floodlight**

Technical parameter  
 Rated voltage: AC220V/50Hz  
 Rated power (metal halide lamp/sodium lamp)  
 Type A: 1000W/Type B: 400W/Type C: 250W  
 Protection level: IP65  
 Weight: Type A: 21.5kg/B: 9.15/C: 8.36

**CRG9887 mining light**

Technical parameter  
 Rated voltage: AC220V  
 Power: 100/150/200W  
 Protection level: IP65

**CRG9603 anti glare floodlight**

Technical parameter  
 Rated voltage: AC220V/50Hz  
 Rated power: 150W (metal halide lamp/sodium lamp)  
 Protection level: IP65  
 Weight: 6kg

**CRG9600 anti glare street lamp**

Technical parameter  
 Rated voltage: AC220V/50Hz  
 Rated power (metal halide lamp/sodium lamp):  
 250W/400W  
 Protection level: IP65  
 Weight: 14kg

**CRG9601 anti glare street lamp**

Technical parameter  
 Rated voltage: AC220V/50Hz  
 Rated power (metal halide lamp/sodium lamp):  
 150W/70W  
 Protection level: IP65  
 Weight: 4.5kg

**CRG9605 Anti glare Ceiling Light**

Technical parameter  
 Rated voltage: AC220V/50Hz  
 Rated power: 150W (metal halide lamp)  
 Protection level: IP65  
 Weight: 4.5kg

**CRG9888 LED floodlight**

Technical parameter  
 Frequency range: 50Hz/60Hz  
 Light source power (LED): 100W  
 Protection level: IP66  
 Net weight: 3.3Kg



Visit Factory

360° VR panoramas we provide

---

<http://www.yrftextile.com>

Email: [info@yrftextile.com](mailto:info@yrftextile.com)

Whatsapp: +8613702995607